

PRODUCT SPECIFICATION SHEET



THE SK SERIES



Electric heater with fireclay core, VDE-GS tested and CE certified. Pure white (RAL 9010), powder coated sheet steel housing. High quality heating conductor embedded in fireclay storage stones. Impregnated, moisture repellent fireclay storage stones. Automatic thermal cut-out integrated in the appliance. Wall mounting set in heater paint included in the delivery scope. Castors or feet for setting up the heater can be included in the delivery scope as an option. Other housing colours are possible/available in accordance with the RAL colour chart.

Control accessories: external room thermostat/timer thermostat, external thermostat adapter, additional control options on request

Indication of the depth always plus 3 cm for wall mounting



THE SK SERIES IN FIGURES

Typ	Operating mode	Supply voltage V	Output W	Protection A	Height/Width/Depth cm	Weight Kg
SK 100	electric	230	1000	6	23 / 68,5 / 13	18
SK 150	electric	230	1500	10	23 / 99 / 13	25
SK 200	electric	230	2000	10	23 / 133 / 13	32
SK 250	electric	230	2500	16	23 / 162,5 / 13	39

THE SN SERIES

Electric heater with fireclay core, VDE-GS tested and CE certified. Pure white (RAL 9010), powder coated sheet steel housing. High quality heating conductor embedded in fireclay storage stones. Impregnated, moisture repellent fireclay storage stones. Automatic thermal cut-out integrated in the appliance. Wall mounting set in heater paint included in the delivery scope. Castors or feet for setting up the heater can be included in the delivery scope as an option. Other housing colours are possible/available in accordance with the RAL colour chart.

Control accessories: external room thermostat/timer thermostat, built in thermostat on the appliance, built in receiver on the appliance with an external room sensor, external thermostat adapter, additional control options on request

Indication of the depth always plus 3 cm for wall mounting



THE SN SERIES IN FIGURES

Typ	Operating mode	Supply voltage V	Output W	Protection A	Height/Width/Depth cm	Weight Kg
SN 50	electric	230	500	6	38 / 41 / 8	9
SN 100	electric	230	1000	6	38 / 68,5 / 8	18
SN 120	electric	230	1200	6	38 / 99 / 8	27
SN 150	electric	230	1500	10	38 / 99 / 8	27
SN 160	electric	230	1600	10	38 / 133 / 8	36
SN 200	electric	230	2000	10	38 / 133 / 8	36
SN 201	electric	230	2000	10	38 / 162,5 / 8	45
SN 251	electric	230	2500	16	38 / 162,5 / 8	45

THE S SERIES

Electric heater with fireclay core, VDE-GS tested and CE certified. Pure white (RAL 9010), powder coated sheet steel housing. High quality heating conductor embedded in fireclay storage stones. Impregnated, moisture repellent fireclay storage stones. Automatic thermal cut-out integrated in the appliance. Wall mounting set in heater paint included in the delivery scope. Castors or feet for setting up the heater can be included in the delivery scope as an option. Other housing colours are possible/available in accordance with the RAL colour chart.

Control accessories: external room thermostat/timer thermostat, built in thermostat on the appliance, built in receiver on the appliance with an external room sensor, external thermostat adapter, additional control options on request

Indication of the depth always plus 3 cm for wall mounting



THE S SERIES IN FIGURES

Typ	Operating mode	Supply voltage V	Output W	Protection A	Height/Width/Depth cm	Weight Kg
S 50	electric	230	500	6	63 / 41 / 8	19
S 81	electric	230	800	6	63 / 41 / 8	19
S 100	electric	230	1000	6	63 / 68,5 / 8	32
S 120	electric	230	1200	6	63 / 99 / 8	46
S 151	electric	230	1500	10	63 / 99 / 8	46
S 160	electric	230	1600	10	63 / 68,5 / 8	32
S 200	electric	230	2000	10	63 / 133 / 8	58
S 201	electric	230	2000	10	63 / 162,5 / 8	73
S 202	electric	230	2000	10	63 / 99 / 8	46
S 250	electric	230	2500	16	63 / 133 / 8	58
S 251	electric	230	2500	16	63 / 162,5 / 8	73
S 300	electric	230	3000	16	63 / 162,5 / 8	73

THE SD SERIES



Electric heater with fireclay core, VDE-GS tested and CE certified. Pure white (RAL 9010), powder coated sheet steel housing. High quality heating conductor embedded in fireclay storage stones. Impregnated, moisture repellent fireclay storage stones. Automatic thermal cut-out integrated in the appliance. Wall mounting set in heater paint included in the delivery scope. Castors or feet for setting up the heater can be included in the delivery scope as an option. Other housing colours are possible/available in accordance with the RAL colour chart.

Control accessories: external room thermostat/timer thermostat, built in thermostat on the appliance, built in receiver on the appliance with an external room sensor, external thermostat adapter, additional control options on request

Indication of the depth always plus 3 cm for wall mounting

THE SD SERIES IN FIGURES

Typ	Operating mode	Supply voltage V	Output W	Protection A	Height/Width/Depth cm	Weight Kg
SD 100	electric	230	1000	6	63 / 41 / 13	30
SD 125	electric	230	1250	6	63 / 41 / 13	30
SD 150	electric	230	1500	10	63 / 68,5 / 13	58
SD 200	electric	230	2000	10	63 / 68,5 / 13	58
SD 250	electric	230	2500	16	63 / 99 / 13	80
SD 300	electric	230	3000	16	63 / 99 / 13	80



THE SL SERIES



Electric heater with fireclay core, VDE-GS tested and CE certified. Pure white (RAL 9010), powder coated sheet steel housing. High quality heating conductor embedded in fireclay storage stones. Impregnated, moisture repellent fireclay storage stones. Automatic thermal cut-out integrated in the appliance. Wall mounting set in heater paint included in the delivery scope. Other housing colours are possible/available in accordance with the RAL colour chart.

Control accessories: external room thermostat/timer thermostat, built in thermostat on the appliance, built in receiver on the appliance with an external room sensor, external thermostat adapter, additional control options on request

Indication of the depth always plus 3 cm for wall mounting



THE SL SERIES IN FIGURES

Typ	Operating mode	Supply voltage V	Output W	Protection A	Height/Width/Depth cm	Weight Kg
SL 100	electric	230	1000	6	122 / 41 / 8	34
SL 150	electric	230	1500	10	122 / 41 / 8	34
SL 200	electric	230	2000	10	122 / 68,5 / 8	64
SL 250	electric	230	2500	16	122 / 68,5 / 8	64